



Natural
Rubber Latex



Lab & Utility

TouchNTuff®

69-210 69-318 Natural Rubber Latex Glove

Handle the most intricate and delicate products with incredible sensitivity

FEATURES AND BENEFITS:

Comfort, Strength and Sensitivity

The strength and comfort of 100% natural rubber latex, 5 mil thickness for the highest degree of sensitivity

2 versions available to better fit your needs

69-210: Powdered, smooth Grip

69-318: Powder Free, textured finish for better grip

Food compliant

Both the TouchNTuff® 69-210 and 69-318 comply with FDA food handling requirements (21 CFR 177.2600).



WARNING: This product contains natural rubber latex which may cause allergic reactions in some individuals.

*Style 69-318 formerly known as Conform®XT

*Style 69-210 formerly know as Conform®

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

	69-210	69-318
Material	Natural Rubber Latex	
Color	Natural	
Glove Design	Ambidextrous, Powdered, Smooth Grip	Ambidextrous, Powder Free, textured Grip
Cuff	Beaded Cuff	
Audit Standards	ISO 9001:2008, ISO 13485:2003, US FDA 21 CFR PART 820 (QSR), and Canadian MDR	
Quality Control	Incoming for both raw materials and packaging materials, in-process (QA pre-packing inspection) and final release (QA pre-shipment inspection) for all gloves produced.	
Packaging	100 gloves per dispensers, 10 dispensers per shipper carton, 1000 gloves per shipper cartons	
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.	
Country of Origin	Malaysia	

PHYSICAL PROPERTIES:

PROPERTY		TYPICAL VALUES					TESTING METHOD
SIZE		XS 5½ - 6	S 6½ - 7	M 7½ - 8	L 8½ - 9	XL 9½ - 10	
Length (mm)	69-210	NA	240	240	240	240	ASTM D3767/EN 420
	69-318	240	240	240	240	240	
Average Palm Width (mm)	69-210	NA	80	95	102	111	
	69-318	75	85	95	106	116	
Freedom from Holes (Inspection level I)	1.5 AQL					ASTM D5151/EN 374-2	
Palm Thickness Single Wall	(mm: 0.12) / (mils: 4.8)					ASTM D3767/EN 420	
	BEFORE AGING			AFTER AGING			
Ultimate Tensile Strength	Min 18 Mpa			Min 14 Mpa			ASTM D 412-06a
Elongation at Break (%)	Min 650			Min 500			ASTM D 412-06a

ORDERING INFORMATION:

	SIZE	XS	S	M	L	XL
69-210	ASPEN	NA	516704	516705	516706	516707
	ORACLE	NA	104986	104987	104988	104989
69-318	ASPEN	516699	516700	516701	516702	516703
	ORACLE	104985	105072	105073	105074	105075



EN 374



EN 374



CE 0493

For additional information visit us at www.ansell.com, or call us at

North America: +1800 800 0444

Latin America: +55 11 3356 3100

Asia Pacific: +852 2185 0600

Europe: +32 2 528 74 00

Australia: +61 1 800 337 041

® and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2013 All Rights Reserved.