



Nitrile



Lab & Utility

# TouchNTuff®

ADVANCED PRODUCT & WORKER PROTECTION

## 92-616 Nitrile Glove

## Experience lightweight comfort and premium durability

### FEATURES AND BENEFITS:

#### 100% Nitrile

Made of 100% nitrile minimizing Type I skin allergy.

#### Excellent puncture resistance

Offers three times the puncture resistance of standard latex or vinyl gloves.

#### Comfort and Chemical Resistant

Gives a high level of protection against hydrocarbons, fats, grease and alcohols

#### Grip

Combines excellent fingertip sensitivity with exceptional durability.

#### Comfort

Lightweight and comfortable to wear.

#### Food Compliant

TouchNTuff® gloves comply with FDA food handling requirements (21 CFR 177.2600).



### TECHNICAL DATA SHEET:

#### PRODUCT INFORMATION:

<b>Material</b>	Nitrile
<b>Color</b>	Light Blue
<b>Glove Design</b>	Ambidextrous, Powder Free, Finger textured
<b>Cuff</b>	Beaded Cuff
<b>Audit Standards</b>	ISO 9001, ISO 13485
<b>Quality Control</b>	FDA 21 CFR 177-2600
<b>Packaging</b>	150 gloves per dispensers, 10 dispensers per shipper carton, 1500 gloves per shipper cartons
<b>Storage</b>	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
<b>Country of Origin</b>	Malaysia

#### PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES					TESTING METHOD
SIZE	XS 5½-6	S 6½-7	M 7½-8	L 8½-9	XL 9½-10	ASTM D3767/EN 420
Length (mm)	240	240	240	240	240	
Average Palm Width (mm)	75	85	95	106	116	

Freedom from Holes (Inspection level I)	1.5 AQL	ASTM D412-06a	
Palm Thickness Single Wall	(mm: 0.08) / (mils: 3)	ASTM D3767/EN 420	
	<b>BEFORE AGING</b>	<b>AFTER AGING</b>	
Ultimate Tensile Strength	Min 14 Mpa	Min 14 Mpa	ASTM D 412-06a
Elongation at Break (%)	Min 500	Min 400	ASTM D 412-06a

#### ORDERING INFORMATION:

SIZE	XS 5½-6	S 6½-7	M 7½-8	L 8½-9	XL 9½-10
<b>ASPN</b>	586312	586313	586314	586315	586316
<b>ORACLE</b>	105130	105131	105132	105133	105134

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at  
 North America, Latin America and Caribbean: +1800 800 0444  
 Asia Pacific: +852 2185 0600  
 Europe: +32 2 528 74 00  
 Australia: +61 3 9270 7270

® and ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2013 All Rights Reserved.