

Product protection in Class 10/ISO 4 environments



Low Particulate Levels

The Ansell Nitrilite® glove range offers two levels of cleanliness. Produced in a controlled powder-free environment, they feature exceptionally low levels of extractable and particles for excellent product protection.

Packed Clean To Stay Clean

Packed in a class 100 environment, double bagged in clean room compatible packaging and then packed into a lined shipper carton. Printed using IPA-resistant ink.

Excellent Electrical Properties

Well suited for electrically sensitive applications requiring low particulate and superior hand protection.

Fit, Comfort and Dexterity

The soft, flexible polymer formulation allows for an improved user fit for longer term wearing comfort.

Prevention from Type I Allergies

Contains no natural rubber proteins, therefore protects against Type I skin allergies.

Certified Quality and Traceability

All lots are supported with Certificate of Certification (CoC) traceability and quality monitoring.



Industries

- Electronics Manufacturing
- Medical Laboratories
- Pharmaceutical
- Research Laboratories

Applications

- Acid Resistance
- Assembly and inspection
- Chemical handling
- Filtration processes
- Laboratory analysis
- Light assembly tasks
- Light duty maintenance

TECHNICAL DATA SHEET:

PRODUCT INFORMATION:

Material	100% Nitrile polymer, manufactured in a clean environment
Color	Natural
Glove Design	Ambidextrous and textured fingers
Cuff	Rolled, beaded cuff
Clean Room Compatibility	Gloves are double-wrapped in cleanroom-compatible packaging and packed in a lined shipping carton. Recommended for ISO 4 areas.
Audit Standards	ISO 9002
Quality Control	EN 420, EN 374-1, EN 374-2, EN 374-3, FDA 21 CFR 177-2600
Packaging	50 Gloves per polybag, 2 polybags per Master polybag, 10 Master Polybags per case. 1000 gloves per case. Packaging and labeling is printed with IPA-resistant ink. The gloves are doublebagged for superior contamination control. Packed in a Class 100 cleanroom.
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia

PHYSICAL PROPERTIES:

PROPERTY	TYPICAL VALUES						TESTING METHOD
	XS 5-5½	S 6-6½	M 7-7½	L 8-8½	XL 9-9½	XXL 10-10½	
Length (mm / inches)	300/11.8	300/11.8	300/11.8	300/11.8	300/11.8	300/11.8	ASTM D3767/EN 420
Average Palm Width (mm)	75	85	95	105	115	125	
Freedom from Holes (Inspection level I)	1.5 AQL						ASTM D5151/EN 374-2
Palm Thickness Single Wall	(mm: 0.11) / (mils: 4.3)						ASTM D3767/EN 420
Particle Count	≤ 400						IEST-RP-CC005.2-7

	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength	≥ 18 Mpa	NA	ASTM D 412-06a
Elongation at Break (%)	≥ 500	NA	ASTM D 412-06a
Modulus @ 300% (MPa)	≤ 9	NA	ASTM D 412-06a

IONIC CONTENT	SPECIFICATION	TYPICAL	IONIC CONTENT	SPECIFICATION	TYPICAL
Aluminum (Al ³⁺)	<0.020 µg/cm ²	<0.010 µg/cm ²	Nitrate (NO ₃ ⁻)	<0.100 µg/cm ²	0.0235 µg/cm ²
Chloride (Cl ⁻)	<0.200 µg/cm ²	0.05 µg/cm ²	Potassium (K ⁺)	<0.020 µg/cm ²	0.0099 µg/cm ²
Copper (Cu ²⁺)	<0.01 µg/cm ²	<0.0004 µg/cm ²	Silicone (Mg/Cm ³)	ND	ND
Iron (Fe ³⁺)	<0.020 µg/cm ²	<0.010 µg/cm ²	Sodium (Na ⁺)	<0.050 µg/cm ²	0.014 µg/cm ²
Lithium (Li ⁺)	<0.0001 µg/cm ²	<0.0001 µg/cm ²	Sulfate (SO ₄ ²⁻)	<0.010 µg/cm ²	0.0095 µg/cm ²
Magnesium (Mg ²⁺)	<0.005 µg/cm ²	<0.001 µg/cm ²	Zinc (Zn ²⁺)	<0.05 µg/cm ²	0.0096 µg/cm ²

Test methods per IEST-RP-CC005.2 using an orbital shaker. ND=None Detected

ORDERING INFORMATION:

SIZE	XS 5-5.5	S 6-6.5	M 7-7.5	L 8-8.5	XL 9-9.5	XXL 10-10.5
NA/LAC ASPN	365757	365758	365759	365760	365761	365772
NA/LAC Oracle	104945	104946	104947	104948	104949	104955
EMEA/APAC ASPN	388814	388806	388807	388808	388809	388810

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

Europe
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
+32 2 528 74 00
+32 2 528 74 01

Asia Pacific
Ansell Global Trading
Center (Malaysia) Sdn Bhd
Prima 6, Prima Avenue
Block 3512, Jalan Teknokrat 6
63000 Cyberjaya
Selangor, Malaysia
T: +60 3 83106688
F: +60 3 8318 6699

North America
Ansell Protective Products Inc.
111 Wood Avenue South,
Suite 210
Iselin, NJ 08830, USA
+1 800 800 0444
+1 800 800 0445

Latin America
Ansell Brazil Ltda
Rua das Figueiras 474 - 4º Andar
Bairro Jardim
SP 09080-300 Santo André
Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100

Australia
Ansell Limited
Level 3, 678 Victoria Street,
Richmond, Vic, 3121
Australia
+61 1800 337 041
+61 1800 803 578

Russia
Анселл РУС
123610 Россия, Москва
Краснопресненская
Наб. 12, п.3, оф. 1304А
Тел. +7 495 258 13 16

Regulatory Compliance



Performance Standards

